

The logo for PAINT TEK features the words "PAINT" and "TEK" in a bold, blue, sans-serif font. A small white square is positioned above the letter 'A' in "PAINT". The logo is set against a yellow background.

SURFACE SOLUTIONS

ACN 107450644
P.O Box 1328
Factory 4/1
Narre Warren (Vic) 3805
Melbourne, Australia
Mobile: 0413736762
Phone/Fax: 0061(03)97967020
Paintek@alphalink.com

	<i>Multicolour water-in-water finish</i>
ISSUE DATE	January 2005
USED FOR	Decorative effect. Special effect. Disguising surface defects
GENERIC TYPE	Acrylic water based
DESCRIPTION	Fully water based with discrete colour separation.
FEATURES	Unique effects, most colours possible, most colour combinations possible
SPECIAL FEATURES	Excellent adhesion, light stable, durable, tough, scrubbable, excellent opacity.
VARIATIONS POSSIBLE	Degree of mixing, application method, colour, ratio of colours, number of colours, reduction with diluent, application over basecoat colour,
COLOUR	Most decorative house paint colours
SUGGESTED ADDITIONS	Clear diluent acrylic, mica flake, glass beads, fine sand, glass fibre metal flake
INDUSTRY	Architectural, industrial, automotive, marine, antigraffiti
SUBSTRATE	Wood, wall board, primed metal, concrete, fibreglass
METHOD OF APPLICATION	Spray gun, roller, brush and trowel
GLOSS	Matt
DRY TIME	Touch dry :1-2 hours @ 20 °C / Hard dry :overnight @ 20 °C
VISCOSITY	Paste/ gel consistency

